



IDS Lift-Net Tech Support

>>> IDS / Lift-Net Tech Bulletin <<<

IDS recommended wire for ALL DATA network applications including Ethernet, Lift-Net and all other RS485, and all RS422 applications has changed to the following Un-shielded four twisted pair Category 6 cable:

Standard - Non-plenum (run inside conduit or duct) applications:

BELDEN part number 1872A-A1000-6

Newark Electronics Stock number 01F166

CATEGORY 6, MEDIATWIST, MULTIMEDIA LAN CABLE, NON PLENUM, DRAFT 5, BLUE, 24 AWG CONDUCTOR SIZE, 27.4 OHM/1000 FOOT RESISTANCE, 25 DB/M AT 100 MHZ MINIMUM PS-ACR, 42.3 DB AT 100 MHZ MINIMUM

\$166.45 per Spool of 1,000 ft.

Plenum rated (run external to conduit or duct) applications:

BELDEN part number 1874A-A1000-D15

Newark Electronics Stock number 01F168

CATEGORY 6, MEDIATWIST; MULTIMEDIA LAN CABLE, PLENUM, BLUE, 24 AWG CONDUCTOR SIZE, 27.4 OHM/1000 FOOT RESISTANCE, 25 DB/M AT 100 MHZ MINIMUM PS-ACR, 42.3 DB AT 100 MHZ MINIMUM

\$480.02 per Spool of 1,000 ft.

Wire for Lift-Net Voice analog audio channel only will continue to be Shielded 4 Twisted Pair cable -

CDT manufacturers part number M54783

Newark Stock # - 91F9290

Please contact Lift-Net Tech Support for further information
847 475 2476